

ICBCL3650F/S



FEATURES

ClearSight™ LED lighting system fully illuminates the interior and reduces shadows

Sleek stainless accents trim the interior, matching the sophistication of the exterior

Touch control panel is conveniently located for easy access at the tap of a finger

Night Mode optimizes the interior lighting based on the detected ambient light, reducing the brightness by 90% in dim environments

Position adjustable door bins at various heights to accommodate assorted items

The removable ice bin with articulating handle ensures portable, easy access to ice

Fresh-tasting, odorless, filtered ice ready on-demand and activate Max Ice Mode to temporarily increase ice production

Stainless-Steel exterior and Pro or Tubular handles to match other Sub-Zero and Wolf products

ACCESSORIES

90° Door Stop

Dual Installation Kit

1676 mm and 1829 mm Dual Wide Grille with Dual Installation Kit

Egg Container

Stainless Steel Side Panel

Stainless Steel Kickplate

Mounting Kit for Custom Side Panel

Replacement Water Filter

Accessories are available through an authorized dealer.
For local dealer information, visit subzero-wolf.com/hk



HANDLE OPTIONS

PRO



TUBULAR



PRODUCT DETAILS


FREEZER

- 4 stainless-steel freezer shelves (3 adjustable; 1 stationary)
- 3 storage drawers with adjustable dividers
- 5 adjustable door bins
- Automatic ice maker with removable ice bin with handle
- Water filtration system


PRODUCT SPECIFICATIONS

Model	ICBCL3650F/S
Dimensions	914 mm W x 2134 mm H x 610 mm D
Door Clearance	946 mm
Freezer Capacity	571 L
Shipping Weight	206 kg
Electrical Supply	220-240 VAC; 50/60 Hz
Electrical Service	1.7 A
Water Pressure	2.4-8.3 bar
Receptacle	3-prong grounding-type
Electrical Cord	2 m

ELECTRICAL



PLUMBING




NOTE: Dimensions in parenthesis are in millimeters unless otherwise specified

INTERIOR VIEW




This illustration is intended for interior reference only and may not represent the exterior of the model being specified.

DIMENSIONS



STANDARD INSTALLATION



NOTE: 3 1/2" (89) finished returns will be visible and should be finished to match cabinetry
Shaded line represents profile of unit.